



Temp. Range: -10 °C to 60°C

Applications: Applied to the lines of the auxiliaries for agricultural tools against the drought, project, mining, environment protection, industry and so on.

Construction:

- (1) Light weight, good flexibility, bright color, smooth smearing layer.
- (2) Flat roll and easy for take back, convenient for moving and non limitation for length.
- (3) Capable for keeping the flexibility and elasticity under the low-temperature water.
- (4) Anti-hi pressure, corrosion resistance and ageing resistance.

PVC Layflat Hose with Standard Duty

Part No.	size	Inner Diameter		Working Pressure		Weight		Length
		inch	mm	Psi	Bar	lb./ft.	kg/m	m/coil
SH4025	1"	0.984	Φ25	110-125	7 ~ 8	0.10	0.15	100
SH4032	1-1/4"	1.260	Φ32	90-110	6 ~ 7	0.11	0.17	100
SH4038	1-1/2"	1.496	Φ38	90-110	6 ~ 7	0.13	0.20	100
SH4050	2"	1.969	Φ50	75-90	5 ~ 6	0.19	0.28	100
SH4065	2-1/2"	2.559	Φ65	60-75	4 ~ 5	0.20	0.30	100
SH4075	3"	2.953	Φ75	60-75	4 ~ 5	0.31	0.46	100
SH4102	4"	4.016	Φ102	45-60	3 ~ 4	0.42	0.62	100
SH4125	5"	4.921	Φ125	45-60	3 ~ 4	0.50	0.75	100
SH4150	6"	5.906	Φ150	30-45	2 ~ 3	0.60	0.90	100
SH4200	8"	7.874	Φ200	15-30	1 ~ 2	1.07	1.60	100

PVC Layflat Hose With Heavy Duty

Part No.	size	Inner Diameter		Working Pressure		Weight		Length
		inch	mm	Psi	Bar	lb./ft.	kg/m	m/coil
SH6025	1"	0.984	Φ25	125-130	8 ~ 9	0.12	0.18	100
SH6032	1-1/4"	1.260	Φ32	110-125	7 ~ 8	0.14	0.21	100
SH6038	1-1/2"	1.496	Φ38	110-125	7 ~ 8	0.20	0.30	100
SH6050	2"	1.969	Φ50	90-110	6 ~ 7	0.23	0.35	100
SH6065	2-1/2"	2.559	Φ65	75-90	5 ~ 6	0.27	0.40	100
SH6075	3"	2.953	Φ75	75-90	5 ~ 6	0.37	0.55	100
SH6102	4"	4.016	Φ102	60-75	4 ~ 5	0.48	0.72	100
SH6125	5"	4.921	Φ125	60-75	4 ~ 5	0.67	1.00	100
SH6150	6"	5.906	Φ150	45-60	3 ~ 4	0.74	1.10	100
SH6200	8"	7.874	Φ200	30-45	2 ~ 3	1.21	1.80	100