



Temp. Range: -10 °C to 65°C

Applications: To be used for discharging and conveying water, oil and powder in factories, agriculture and engineering.

Construction:

- (1) Good transparency and easy monitoring liquid flow.
- (2) Small bending radius and great ability of minus pressure resistance.

Part No.	Size	Inner Diameter		Outer Diameter		weight		Length (m/coil)
		inch	mm	inch	mm	lb./ft.	kg/m	
SHSS00813	5/16"	0.31	8	0.51	13	0.09	0.13	100
SHSS00815		0.31	8	0.59	15	0.13	0.20	
SHSS00915	3/8"	0.35	9	0.59	15	0.12	0.18	
SHSS00916		0.35	9	0.63	16	0.14	0.21	
SHSS01218	1/2"	0.47	12	0.71	18	0.15	0.22	
SHSS01318		0.51	13	0.71	18	0.13	0.19	
SHSS01319		0.51	13	0.75	19	0.15	0.23	
SHSS01522		0.59	15	0.87	22	0.21	0.31	
SHSS01622	5/8"	0.63	16	0.87	22	0.18	0.27	
SHSS01623		0.63	16	0.91	23	0.22	0.33	
SHSS01924	3/4"	0.75	19	0.94	24	0.17	0.26	
SHSS01925		0.75	19	0.98	25	0.21	0.31	
SHSS01926		0.75	19	1.02	26	0.25	0.38	
SHSS01928		0.75	19	1.10	28	0.34	0.50	
SHSS02529	1"	0.98	25	1.14	29	0.17	0.26	
SHSS02530		0.98	25	1.18	30	0.22	0.33	
SHSS02531		0.98	25	1.22	31	0.27	0.40	
SHSS02532		0.98	25	1.26	32	0.32	0.48	
SHSS02533	1-1/4"	0.98	25	1.30	33	0.37	0.55	
SHSS03238		1.26	32	1.50	38	0.34	0.50	
SHSS03239		1.26	32	1.54	39	0.40	0.60	
SHSS03240		1.26	32	1.57	40	0.47	0.70	
SHSS03241	1-1/2"	1.26	32	1.61	41	0.54	0.80	
SHSS03844		1.50	38	1.73	44	0.40	0.60	
SHSS03845		1.50	38	1.77	45	0.47	0.70	
SHSS03846		1.50	38	1.81	46	0.54	0.80	
SHSS03847	1-5/8"	1.50	38	1.85	47	0.60	0.90	
SHSS04047		1.57	40	1.85	47	0.49	0.73	
SHSS04049		1.57	40	1.93	49	0.64	0.96	
SHSS04553		1-3/4"	1.77	45	2.09	53	0.60	0.90
SHSS04555	1.77		45	2.17	55	0.80	1.20	
SHSS04556	1.77		45	2.20	56	0.89	1.33	
SHSS04557	1.77		45	2.24	57	0.98	1.46	
SHSS05058	2"	1.97	50	2.28	58	0.67	1.00	
SHSS05059		1.97	50	2.32	59	0.80	1.20	
SHSS05060		1.97	50	2.36	60	0.87	1.30	
SHSS05061		1.97	50	2.40	61	0.97	1.44	
SHSS05062	2-5/16"	1.97	50	2.44	62	1.07	1.60	
SHSS05160		2.01	51	2.36	60	0.80	1.20	
SHSS05161		2.01	51	2.40	61	0.90	1.34	
SHSS05162		2.01	51	2.44	62	0.99	1.48	
SHSS05163	2-3/8"	2.01	51	2.48	63	1.09	1.63	
SHSS05868		2.28	58	2.68	68	1.01	1.50	
SHSS05869		2.28	58	2.72	69	1.12	1.67	
SHSS05870		2.28	58	2.76	70	1.23	1.83	
SHSS06070	2-1/2"	2.36	60	2.76	70	1.04	1.55	
SHSS06071		2.36	60	2.80	71	1.15	1.72	
SHSS06072		2.36	60	2.83	72	1.27	1.89	
SHSS06073		2.36	60	2.87	73	1.34	2.00	
SHSS06074	3"	2.36	60	2.91	74	1.50	2.24	
SHSS06474		2.52	64	2.91	74	1.11	1.65	
SHSS06475		2.52	64	2.95	75	1.22	1.82	
SHSS06478		2.52	64	3.07	78	1.59	2.37	
SHSS07584	3-1/2"	2.95	75	3.31	84	1.14	1.70	
SHSS07585		2.95	75	3.35	85	1.27	1.90	
SHSS07586		2.95	75	3.39	86	1.41	2.10	
SHSS07587		2.95	75	3.43	87	1.54	2.30	
SHSS07590	4"	2.95	75	3.54	90	1.95	2.90	
SHSS08999		3.50	89	3.90	99	1.48	2.20	
SHSS089101		3.50	89	3.98	101	1.81	2.70	
SHSS090102		3.54	90	4.02	102	1.84	2.75	
SHSS090104	4-1/4"	3.54	90	4.09	104	2.15	3.20	
SHSS102112		4.02	102	4.41	112	1.74	2.60	
SHSS102114		4.02	102	4.49	114	2.08	3.10	
SHSS102118		4.02	102	4.65	118	2.82	4.20	
SHSS102120	5"	4.02	102	4.72	120	3.22	4.80	
SHSS102122		4.02	102	4.80	122	3.62	5.40	
SHSS110123		4.33	110	4.84	123	2.41	3.60	
SHSS110124		4.33	110	4.88	124	2.62	3.90	
SHSS110127	6"	4.33	110	5.00	127	3.22	4.80	
SHSS127143		5.00	127	5.63	143	3.42	5.10	
SHSS127144		5.00	127	5.67	144	3.69	5.50	
SHSS152168		8"	5.98	152	6.61	168	4.06	6.05
SHSS152170	5.98		152	6.69	170	4.36	6.50	
SHSS200220		7.87	200	8.66	220	7.38	11.00	