



Acetylene Hose



Tube: black, smooth, synthetic rubber
 Reinforcement: high tensile synthetic yarn braided or spiraled
 Application: for conveying welding gases.
 Cover: red or blue, smooth(streaky finish) synthetic rubber, abrasion, weather and abrasion resistant
 Temp Range: -35°C to 90°C

I.D.		O.D.	W.P.		B.P.		WEIGHT	LENGTH MAX.
MM	INCH	MM	MPA	PSI	MPA	PSI	KG/M	M/ROLL
5	3/16"	12	1.0~ 2.0	145~ 290	3.0~ 6.0	430~ 870	0.13	100±1%
6	1/4"	13	1.0~ 2.0	145~ 290	3.0~ 6.0	430~ 870	0.15	100±1%
8	5/16"	15	1.0~ 2.0	145~ 290	3.0~ 6.0	430~ 870	0.23	100±1%
10	3/8"	17	1.0~ 2.0	145~ 290	3.0~ 6.0	430~ 870	0.26	100±1%
13	1/2"	22	1.0~ 2.0	145~ 290	3.0~ 6.0	430~ 870	0.36	100±1%
16	5/8"	25	1.0~ 2.0	145~ 290	3.0~ 6.0	430~ 870	0.53	100±1%
19	3/4"	29	1.0~ 2.0	145~ 290	3.0~ 6.0	430~ 870	0.64	100±1%



Twin Welding Hose



Tube: black, smooth, synthetic rubber
 Reinforcement: high tensile synthetic yarn braided or spiraled
 Cover: blue and red, smooth synthetic rubber, abrasion, weather and abrasion resistant
 Application: for conveying welding gases.
 Temp. Range: -35°C to 90°C

I.D.		O.D.	W.P.		B.P.		WEIGHT	LENGTH MAX.
MM	INCH	MM	MPA	PSI	MPA	PSI	KG/M	M/ROLL
5	3/16"	12	1.0~ 2.0	145~ 290	3.0~ 6.0	430~ 870	0.13	100±1%
6	1/4"	13	1.0~ 2.0	145~ 290	3.0~ 6.0	430~ 870	0.15	100±1%
8	5/16"	15	1.0~ 2.0	145~ 290	3.0~ 6.0	430~ 870	0.23	100±1%
10	3/8"	17	1.0~ 2.0	145~ 290	3.0~ 6.0	430~ 870	0.26	100±1%
13	1/2"	22	1.0~ 2.0	145~ 290	3.0~ 6.0	430~ 870	0.36	100±1%



LPG Hose



Tube: black, smooth, nitrile rubber
 Reinforcement: high tensile synthetic yarn braided or spiraled
 Cover: orange, smooth (wrapped finish) synthetic rubber, abrasion, weather and oil mist resistant
 Application: for conveyance of liquid gas, home burner system, grill, oil-resistant

I.D.		O.D.	W.P.		B.P.		WEIGHT	LENGTH MAX.
MM	INCH	MM	MPA	PSI	MPA	PSI	KG/M	M/ROLL
5	3/16"	12	1.0~ 2.0	145~ 290	3.0~ 6.0	430~ 870	0.13	100±1%
6	1/4"	13	1.0~ 2.0	145~ 290	3.0~ 6.0	430~ 870	0.15	100±1%
8	5/16"	15	1.0~ 2.0	145~ 290	3.0~ 6.0	430~ 870	0.23	100±1%
10	3/8"	17	1.0~ 2.0	145~ 290	3.0~ 6.0	430~ 870	0.26	100±1%
13	1/2"	22	1.0~ 2.0	145~ 290	3.0~ 6.0	430~ 870	0.36	100±1%