



Fule Oil Hose



Tube: black, smooth, nitrile rubber

Reinforcement: high tensile synthetic yarn braided or spiraled

Cover: black, smooth (wrapped finish) synthetic rubber, abrasion, weather and oil mist resistant
Application: use on hydraulic systems such as oil return hose, can also be used for various petroleum products

Temp Range: -40°C to 100°C

I.D.		O.D.	W.P.		B.P.		WEIGHT	LENGTH MAX.
MM	INCH	MM	MPA	PSI	MPA	PSI	KG/M	M/ROLL
5	3/16"	12	0.3~ 1.0	45~ 145	0.9~ 3.0	130~ 430	0.13	100±1%
6	1/4"	13	0.3~ 1.0	45~ 145	0.9~ 3.0	130~ 430	0.15	100±1%
8	5/16"	15	0.3~ 1.0	45~ 145	0.9~ 3.0	130~ 430	0.23	100±1%
10	3/8"	17	0.3~ 1.0	45~ 145	0.9~ 3.0	130~ 430	0.26	100±1%
13	1/2"	22	0.3~ 1.0	45~ 145	0.9~ 3.0	130~ 430	0.36	100±1%
16	5/8"	25	0.3~ 1.0	45~ 145	0.9~ 3.0	130~ 430	0.53	100±1%
19	3/4"	29	0.3~ 1.0	45~ 145	0.9~ 3.0	130~ 430	0.64	100±1%
25	1"	36	0.3~ 1.0	45~ 145	0.9~ 3.0	130~ 430	0.85	100±1%
32	1.1/4"	43	0.3~ 1.0	45~ 145	0.9~ 3.0	130~ 430	1.2	50±1%
38	1.1/2"	50	0.3~ 1.0	45~ 145	0.9~ 3.0	130~ 430	1.39	50±1%
51	2"	65	0.3~ 1.0	45~ 145	0.9~ 3.0	130~ 430	1.8	50±1%



Oxygen Hose



Tube: black, smooth, synthetic rubber

Reinforcement: high tensile synthetic yarn braided or spiraled

Application: for conveying welding gases.

Cover: blue or black smooth (streaky finish) synthetic rubber, abrasion, weather and abrasion resistant

Temp Range: -35°C to 90°C

I.D.		O.D.	W.P.		B.P.		WEIGHT	LENGTH MAX.
MM	INCH	MM	MPA	PSI	MPA	PSI	KG/M	M/ROLL
5	3/16"	12	1.0~ 2.0	145~ 290	3.0~ 6.0	430~ 870	0.13	100±1%
6	1/4"	13	1.0~ 2.0	145~ 290	3.0~ 6.0	430~ 870	0.15	100±1%
8	5/16"	15	1.0~ 2.0	145~ 290	3.0~ 6.0	430~ 870	0.23	100±1%
10	3/8"	17	1.0~ 2.0	145~ 290	3.0~ 6.0	430~ 870	0.26	100±1%
13	1/2"	22	1.0~ 2.0	145~ 290	3.0~ 6.0	430~ 870	0.36	100±1%
16	5/8"	25	1.0~ 2.0	145~ 290	3.0~ 6.0	430~ 870	0.53	100±1%
19	3/4"	29	1.0~ 2.0	145~ 290	3.0~ 6.0	430~ 870	0.64	100±1%
25	1"	36	1.0~ 2.0	145~ 290	3.0~ 6.0	430~ 870	0.85	100±1%