



**Temp. Range:** -10 °C to 65°C

**Applications:** drawing and conveying water, oil and powder in factory, agriculture, building. and so on.

**Construction:**

- (1) Transparent and good cold and hot resistance.
- (2) Small bending radius and great ability of minus pressure resistance.

Part No.	size	Inner Diameter		Thickness (mm)	Weight		Length (m/ coil)
		inch	mm		lb./ ft.	kg/m	
SHS1320	1/2"	0.53	13.5	2	0.08	0.12	30
SHS1325				2.5	0.10	0.15	30
SHS1330				3	0.12	0.18	30
SHS1335				3.5	0.15	0.22	30
SHS1920	3/4"	0.75	19	2	0.12	0.18	30
SHS1925				2.5	0.15	0.23	30
SHS1930				3	0.19	0.28	30
SHS1935				3.5	0.21	0.32	30
SHS2520	1"	0.98	25	2	0.15	0.23	30
SHS2525				2.5	0.19	0.29	30
SHS2530				3	0.23	0.35	30
SHS2535				3.5	0.28	0.41	30
SHS3025	1.2"	1.18	30	2.5	0.23	0.35	30
SHS3030				3	0.28	0.42	30
SHS3035				3.5	0.34	0.5	30
SHS3040				4	0.38	0.56	30
SHS3225	1-1/4"	1.26	32	2.5	0.25	0.38	30
SHS3230				3	0.31	0.46	30
SHS3235				3.5	0.37	0.55	30
SHS3240				4	0.42	0.62	30
SHS3825	1-1/2"	1.50	38	2.5	0.30	0.44	30
SHS3830				3	0.36	0.53	30
SHS3835				3.5	0.42	0.62	30
SHS3840				4	0.48	0.71	30
SHS4325	1-3/4"	1.69	43	2.5	0.34	0.5	30
SHS4330				3	0.41	0.61	30
SHS4335				3.5	0.47	0.7	30
SHS4340				4	0.54	0.8	30
SHS5030	2"	1.97	50	3	0.47	0.7	30
SHS5035				3.5	0.55	0.82	30
SHS5040				4	0.64	0.95	30
SHS5045				4.5	0.74	1.1	30
SHS6330	2-1/2"	2.48	63	3	0.59	0.88	30
SHS6335				3.5	0.70	1.04	30
SHS6340				4	0.80	1.19	30
SHS6345				4.5	0.93	1.38	30
SHS7535	3"	2.95	75	3.5	0.80	1.2	30
SHS7540				4	0.93	1.38	30
SHS7545				4.5	1.05	1.56	30
SHS7550				5	1.21	1.8	30
SHS8835	3-1/2"	3.46	88	3.5	0.89	1.32	30
SHS8840				4	1.02	1.52	30
SHS8845				4.5	1.15	1.71	30
SHS8850				5	1.34	2	30
SHS10040	4"	3.94	100	4	1.11	1.66	30
SHS10045				4.5	1.26	1.88	30
SHS10050				5	1.40	2.09	30
SHS10055				5.5	1.54	2.3	30
SHS11340	4-1/2"	4.45	113	4	1.23	1.83	30
SHS11345				4.5	1.38	2.06	30
SHS11350				5	1.60	2.38	30
SHS11355				5.5	1.88	2.8	30
SHS12545	5"	4.92	125	4.5	1.74	2.59	30
SHS12550				5	1.93	2.88	30
SHS12555				5.5	2.13	3.18	30
SHS12560				6	2.35	3.5	30
SHS15050	6"	5.91	150	5	2.35	3.5	30
SHS15060				6	2.75	4.1	30
SHS15070				7	3.21	4.79	30
SHS15080				8	3.69	5.5	30
SHS20060	8"	7.87	200	6	3.42	5.1	30
SHS20070				7	3.96	5.9	30
SHS20080				8	4.56	6.8	30
SHS20090				9	5.08	7.58	30